

NEW



SERIE **023S.06**

PNEUMATIC COUPLINGS
PNEUMATISCHE KUPPLUNGEN



SAFETY COUPLING WITH PUSH BUTTON
SICHERHEITSKUPPLUNG MIT DRUCKKNOPF

Interchangeability - Kompatibilität
RECTUS 23, FORSTER, CEJN 310, US MIL STD.
4109 1/4", HANSEN 3000, PARKER LEGRIS
1/4, TST 024 ATLAS COPCO QIC 08, ISO 6150 B

Temperature Range - Temperaturbereich
-20 °C +100 °C (-4 °F +212 °F)

Working Pressure - Betriebsdruck
0 - 12 bar (0 - 508 PSI)

Flow capacity - Nennweite
NW - 5.5

For optional orders please add the symbol
of your option end of the order no.
Bei Bestellungen Kennbuchstabe
bitte hinzufügen.

Material - Material

- Inner Part - Innenteil : Aluminium - Eloxal -
Aluminium - Eloxal
- Back Part - Verschluss : Brass Nickel Plated -
Messing Vernickelt
- Valve - Ventil : Steel Chrome Plated
Stahl Verchromt
- Spring - Feder : Stainless Steel -
Edelstahl
- Coupler Body - Gehäuse : Steel Chrome Plated
Stahl Verchromt
- Seals - Dichtungen : Nitrile (Ni) - NBR
- Balls - Kugeln : AISI 420 Hardened
Edelstahl AISI 420
- Push Button -
Druckknopf : AISI 420 Hardened Steel
Chrome Plated -
Edelstahl AISI 420
Verchromt

Couplers and Plugs
Kupplungen und Nippel


Connection
Anschlüsse

Order No
Bestellnr.

SW


L

ØD




Male Thread Coupling
Kupplung mit Aussengewinde

BSP 1/4"	023.S06 EG 13	20	69	25
BSP 3/8"	023.S06 EG 17	20	72	25
BSP 1/2"	023.S06 EG 21	24	72	25



Female Thread Coupling
Kupplung mit Innengewinde

BSP 1/4"	023.S06 DG 13	20	71	25
BSP 3/8"	023.S06 DG 17	20	73	25
BSP 1/2"	023.S06 DG 21	24	77	25



Standard Hose Barb Coupling
Kupplung mit Schlauchtülle

Ø 6 - 1/4"	023.S06 HG 06	20	86	25
Ø 8 - 5/16"	023.S06 HG 08	20	86	25
Ø 10 - 3/8"	023.S06 HG 10	20	86	25