



**Interchangeability - Kompatibilität**  
CEJN Multi Link

Temperature Range - Temperaturbereich  
-30°C +100°C (-22°F +212°F)

Working Pressure - Betriebsdruck  
0 - 10 bar (0 - 145 PSI)

Material - Material  
Brass Nickel Plated  
Messing vernickelt

**Moduler Link and Accessories - Segment und Zubehör**



Connection  
Anschlüsse

Order No  
Bestellnr.

G 1/2"

117 RK 000 - D21

NPT 1/2"

117 RK 000 - N21

Female Threaded Center Module  
Zwischensegment, Innengewinde



G 1/2"

117 RK D21 - D21

NPT 1/2"

117 RK N21 - N21

Female Threaded Outlet Module  
Endsegment, Innengewinde



G 1/2"

117 RK D21 - 000

NPT 1/2"

117 RK N21 - 000

Inlet Module  
Anfangssegment



117 RK A00 - 000

Stop Valve  
Absperrentil



G 1/2"

KTS 21

NPT 1/2"

KTT 21

Pressure Plug With O-Ring  
Stopfen mit O-Ring



R 1/2"

PUR 21 - 16

NPT 1/2"

PUN 21 - 16

Hose Connection 11 x 16 mm  
Schlauchanschluss 11 x 16 mm



PUR 100.1116

Hose (PUR) 11 x 16 mm 100 m-Rol  
Schlauch (PUR) 11 x 16 mm 100 m-Rolle

**SERIE 117-RK**

