

PNEUMATIC COUPLINGS
PNEUMATISCHE KUPPLUNGEN


SERIE 250

UNIVERSAL COUPLING




Couplers and Plugs
Kupplungen und Nippel

Connection Anschlüsse	Order No Bestellnr.	SW	L	ØD
--------------------------	------------------------	----	---	----




Male Thread Coupling
Kupplung mit Aussengewinde

BSPT 1/4"	250 RG 13	19	60	23
BSPT 3/8"	250 RG 17	19	60	23
BSPT 1/2"	250 RG 21	22	60	23



Female Thread Coupling
Kupplung mit Innengewinde

BSP 1/4"	250 DG 13	19	55	23
BSP 3/8"	250 DG 17	19	55	23
BSP 1/2"	250 DG 21	24	57	23



Standard Hose Barb Coupling
Kupplung mit Schlauchtülle

6 mm - 1/4"	250 HG 06	19	71	23
8 mm - 5/16"	250 HG 08	19	71	23
9 mm - 5/14"	250 HG 09	19	71	23
10 mm - 3/8"	250 HG 10	19	71	23
13 mm - 1/2"	250 HG 13	19	71	23

Interchangeability - Kompatibilität

TST 026, RECTUS 25, RECTUS 26, CEJN 320, and PARKER PEF, JWL 520, JWL 530, Legris RECTUS 23, FORSTER, CEJN 310, US MIL STD. 4109 1/4", HANSEN 3000, PARKER LEGRIS 1/4, TST 024 ATLAS COPCO QIC 08, ISO 6150 B

Temperature Range - Temperaturbereich
-20° C +100° C (-4° F +212° F)

Working Pressure - Betriebsdruck
0 - 35 bar (0 - 508 PSI)

Flow capacity - Nennweite
NW - 7.8

Option - Optionen

F - Straight through flow - ungehinderter Durchfluss
S - Stainless Steel - Edelstahl
V - Viton Seal - Viton Dichtung

Material - Material

Coupler Body-
Kupplungsgrundkörper: Brass Nickel Plated - Messing vernickelt

Back Part - Hinterteil : Steel Nickel Plated - Stahl vernickelt

Sleeve - Hülse : Steel Nickel Plated - Stahl vernickelt

Valve - Ventil : Brass - Messing
Springs - Federn : Stainless Steel - Edelstahl

Locking O-Ring - Sprengring : Stainless Steel - Edelstahl

Balls - Kugeln : Stainless Steel - Edelstahl AISI 420

Seals - Dichtungen : Nitrile (Ni) - NBR (Ni)