









PNEUMATIC COUPLINGS
PNEUMATISCHE KUPPLUNGEN

SERIE 013

SUPER FLOW LINE **SUPERDURCHFLUSS**



Couplers and Plugs Kupplungen und Nippel	Connection Anschlüsse	Order No Bestellnr.	SW	L	ØD
 Male Thread Coupling Kupplung mit Aussengewinde	BSPT 1/4"	013 RG 13	19	65,1	23
	BSPT 3/8"	013 RG 17	19	66,1	23
	BSPT 1/2"	013 RG 21	22	62,1	23
	NPT 1/4"	013 TG 13	19	66,1	23
	NPT 3/8"	013 TG 17	19	67,1	23
	NPT 1/2"	013 TG 21	22	63,1	23
 Female Thread Coupling Kupplung mit Innengewinde	BSP 1/4"	013 DG 13	19	63,1	23
	BSP 3/8"	013 DG 17	19	63,1	23
	BSP 1/2"	013 DG 21	24	65,1	23
	NPT 1/4"	013 NG 13	19	63,1	23
	NPT 3/8"	013 NG 17	19	64,1	23
	NPT 1/2"	013 NG 21	24	65,1	23
 Standard Hose Barb Coupling Kupplung mit Schlauchtülle	Ø 6 mm	013 HG 06	19	77,1	23
	Ø 8 mm	013 HG 08	19	77,1	23
	Ø 10 mm	013 HG 10	19	77,1	23
	Ø 13 mm	013 HG 13	19	76,1	23
 Plastic Hose Coupling Kupplung für Kunststoffschlauch	6 x 10 mm - M 20x1,5	013 PG 06-4	23	72,6	23
	8 x 12 mm - M 20x1,5	013 PG 08-4	23	72,6	23
	9 x 13 mm - M 20x1,5	013 PG 09-4	23	72,6	23
	11 x 16 mm - M 24x1,5	013 PG 11-5	25	72,6	23
 Standard Hose Barb Plug Nippel mit Schlauchtülle	6 mm - 1/4"	013 HU 06		48	14
	8 mm - 5/16"	013 HU 08		48	14
	10 mm - 3/8"	013 HU 10		48	14
	13 mm - 1/2"	013 HU 13		48	15
 Plastic Hose Plug Nippel für Kunststoffschlauch	6 x 10 mm - M 16x1	013 PU 06-4	22	46,5	
	8 x 12 mm - M 16x1	013 PU 08-4	22	46,5	
	9 x 13 mm - M 20x1	013 PU 09-4	22	46,5	
	11 x 16 mm - M 22x1	013 PU 11-5	25	46,5	
 Male Thread Plug Nippel mit Aussengewinde	BSPT 1/8"	013 RU 10	14	37,5	
	BSPT 1/4"	013 RU 13	14	41,5	
	BSPT 3/8"	013 RU 17	17	41,5	
	BSPT 1/2"	013 RU 21	22	44	
	NPT 1/8"	013 TU 10	14	37,5	
	NPT 1/4"	013 TU 13	14	41,5	
	NPT 3/8"	013 TU 17	17	41,5	
NPT 1/2"	013 TU 21	22	44		
 Female Thread Plug Nippel mit Innengewinde	BSP 1/4"	013 DU 13	17	37,5	
	BSP 3/8"	013 DU 17	19	39,5	
	BSP 1/2"	013 DU 21	22	44	
	NPT 1/4"	013 NU 13	17	37,5	
	NPT 3/8"	013 NU 17	19	39,5	
	NPT 1/2"	013 NU 21	22	44	

Interchangeability - Kompatibilität
JAPANESE STANDARD,
RECTUS 13, CEJN 315

Temperature Range Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 30 bar (0 - 435 PSI)

Flow capacity - Nennweite
NW - 7,5

Body Material - Kupplung Material
Stainless Steel - Edelstahl
Nickel plated - N-vernickelt
V - Viton Seal - Viton Dichtung
NPTF thread - T-NPTF-Gewinde
Brass Available

For optional orders please add the symbol of your option end of the order no.
Bei Optionsbestellungen Kennbuchstabe bitte hinzufügen: 013 RG 13-V)

Material - Material

- | | |
|--|---|
| Coupler Body -
Kupplungsgrundkörper : | Steel Nickel Plated -
Stahl vernickelt |
| Sleeve - Hülse | : Steel Nickel Plated -
Stahl vernickelt |
| Valve - Ventil | : Brass - Messing |
| Spring - Federn | : Stainless Steel -
Edelstahl |
| Locking O-Ring -
Sprenging | : Stainless Steel -
Edelstahl |
| Balls Kugeln | : Stainless Steel -
Edelstahl AISI 420L |
| Seals - Dichtungen | : Nitrile (Ni) - NBR (Ni) |
| Plug - Nippel | : Steel Nickel Plated -
Stahl vernickelt |

