



SERIE 051 ■

PNEUMATIC COUPLINGS
PNEUMATISCHE KUPPLUNGEN



SUPER FLOW LINE SUPER DURCHFLUSS

Interchangeability - Kompatibilität
RECTUS 51, WALTER SP 006, SG 006

Temperature Range - Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 35 bar (0 - 508 PSI)

Flow capacity - Nennweite
NW - 6



Option - Optionen

- F - Straight through flow - ungehinderter Durchfluss
- K - Chrome plated - verchromt
- V - Viton Seal - Viton Dichtung
- Z - Zinc Plated - verzinkt

For optional orders please add the symbol of your option end of the order no.
Bei Optionsbestellungen Kennbuchstabe bitte hinzufügen (Beispiel: 051 EG 13-K-V)

Material - Material

- Coupler Body - Kupplungsgrundkörper:** Steel Nickel Plated - Stahl vernickelt
- Back Part - Hinterteil:** Brass Nickel Plated - Messing vernickelt
- Sleeve - Hülse:** Steel Nickel Plated - Stahl vernickelt
- Valve - Ventil:** Brass - Messing
- Springs - Federn:** Stainless Steel - Edelstahl
- Locking O-Ring - Sprengring:** Stainless Steel - Edelstahl
- Pins - Stifte:** Stainless Steel -Edelstahl
- Seals - Dichtungen:** Nitrile (Ni) - NBR (Ni)
- Plug - Nippel:** Steel Hardened Nickel Plated - Stahl gehärtet vernickelt



**Couplers and Plugs
Kupplungen und Nippel**


**Connection
Anschlüsse**

**Order No
Bestellnr.**


SW

L


ØD




BSP 1/4"	051 EG 13	21	60,7	22
BSP 3/8"	051 EG 17	21	60,7	22
BSP 1/2"	051 EG 21	22	63,7	22



BSP 1/4"	051 DG 13	21	62,7	22
BSP 3/8"	051 DG 17	21	62,7	22
BSP 1/2"	051 DG 21	24	63,7	22




6 mm - 1/4"	051 HG 06	21	75	22
9 mm - 5/14"	051 HG 09	21	75	22
11 mm - 7/16"	051 HG 11	21	75	22
13 mm - 1/2"	051 HG 13	21	75	22




Standard Hose Barb Plug
Nippel mit Schlauchtülle

6 mm - 1/4"	051 HU 06		44	
9 mm - 5/14"	051 HU 09		46	
11 mm - 7/16"	051 HU 11		46	
13 mm - 1/2"	051 HU 13		46	



Male Threaded Plug
Nippel mit Aussengewinde

BSP 1/8"	051 EU 10	14	33	
BSP 1/4"	051 EU 13	17	35	
BSP 3/8"	051 EU 17	19	36	
BSP 1/2"	051 EU 21	22	36	



Female Thread Plug
Nippel mit Innengewinde

BSP 1/8"	051 DU 10	14	30	
BSP 1/4"	051 DU 13	17	34	
BSP 3/8"	051 DU 17	19	34	